

	<b>OSAWA</b> <b>NORM</b>	<b>5XD</b> <b>355SU</b> <b>355SUH</b>	<b>8XD</b> <b>358SUH</b>	<b>12XD</b> <b>3512SUH</b>

(m7)

Ø mm	1~3	3.1~6	6.1~10	10.1~18	18.1~20
tol. D µ	+12 / +2	+16 / +4	+21 / +6	+25 / +7	+29 / +8

**NEW**

**NEW**



	<b>PV300</b>	<b>PV300</b>	<b>PV300</b>	<b>PV300</b>

D(m7)	d(h6)	l	L	Stock	Stock	Stock	Stock
mm 1.00	3	6.5	50	○	○	●	●
1.00	3	9.5	50				
1.00	3	13.5	55				
1.05	3	6.5	50	○	○		
1.05	3	10	50			○	
1.10	3	7.2	50	○	○		
1.10	3	10.5	50			●	
1.10	3	14.9	55				○
1.15	3	7.5	50	○	○		
1.15	3	10.9	50			○	
1.20	3	7.8	50	○	○		
1.20	3	11.4	50			●	
1.20	3	16.2	55				●
1.25	3	8.1	50	○	○		
1.25	3	11.9	50			○	
1.28	3	12.4	50			●	
1.30	3	8.5	50	○	○		
1.30	3	12.4	50			●	
1.30	3	17.6	55				●
1.35	3	8.8	50	○	○		
1.35	3	12.8	50			○	
1.40	3	9.1	50	○	○		
1.40	3	13.3	50			●	
1.40	3	18.9	55				○
1.45	3	9.4	50	○	○		
1.45	3	13.8	50			●	
1.50	3	9.8	50	○	○		
1.50	3	14.3	50			●	
1.50	3	20.3	55				●
1.55	3	10.1	50	○	○		
1.55	3	14.7	50			○	
1.60	3	10.4	50	○	○		
1.60	3	15.2	50			●	
1.60	3	21.6	65				●
1.65	3	10.7	55	○	○		
1.65	3	15.7	60			○	

● stock standard ○ non-standard stock ■ stock exhaustion