

 PAGE 246	OSAWA NORM	5XD 355SU 355SUH	8XD 358SUH	12XD 3512SUH

(m7)

Ø mm	1~3	3.1~6	6.1~10	10.1~18	18.1~20
tol. D µ	+12 / +2	+16 / +4	+21 / +6	+25 / +7	+29 / +8



	PV300	PV300	PV300	PV300

D(m7)	d(h6)	l	L	Stock	Stock	Stock	Stock
mm 2.40	3	22.8	60			●	
2.40	3	32.4	75				○
2.45	3	15.9	55	○	○		
2.45	3	23.3	60			○	
2.50	3	16.3	55	○	○		
2.50	3	23.8	60			●	
2.50	3	33.8	75				●
2.55	3	16.6	55	○	○		
2.55	3	24.2	60			○	
2.60	3	16.9	55	○	○		
2.60	3	24.7	60			●	
2.60	3	35.1	75				●
2.65	3	17.2	55	○	○		
2.65	3	25.2	60			○	
2.70	3	17.4	55	○	○		
2.70	3	25.7	60			●	
2.70	3	36.5	75				○
2.75	3	17.9	55	○	○		
2.75	3	26.1	60			○	
2.80	3	18.2	55	○	○		
2.80	3	26.6	60			●	
2.80	3	37.8	75				●
2.85	3	18.5	55	○	○		
2.85	3	27.1	60			○	
2.90	3	18.9	55	○	○		
2.90	3	27.6	60			●	
2.90	3	39.2	75				○
2.95	3	19.2	55	○	○		
2.95	3	28	60			○	

● stock standard ○ non-standard stock ■ stock exhaustion