



DIN 6539

3XD

343TA - 318N (h7)

Ø mm	1~3	3.1~6	6.1~10	10.1~18	18.1~20
tol. D µ	0 / -10	0 / -12	0 / -15	0 / -18	0 / -21



TA

MG

PV200

140°

30°

TA

MG

BR

140°

30°

D(h7)	d(h6)	l	L	Stock	Stock
mm 8.20	8.2	37	79	●	●
8.30	8.3	37	84	●	○
8.40	8.4	37	84	●	○
8.50	8.5	37	84	●	●
8.60	8.6	40	84	●	○
8.70	8.7	40	84	●	●
8.80	8.8	40	84	●	●
8.90	8.9	40	84	●	○
9.00	9	40	84	●	●
9.10	9.1	40	84	●	○
9.20	9.2	40	84	●	●
9.30	9.3	40	89	●	●
9.40	9.4	40	89	●	○
9.50	9.5	40	89	●	●
9.60	9.6	43	89	●	○
9.70	9.7	43	89	●	○
9.80	9.8	43	89	●	●
9.90	9.9	43	89	●	○
10.00	10	43	89	●	●
10.20	10.2	43	89	●	●
10.50	10.5	43	95	●	●
10.80	10.8	47	95	○	●
11.00	11	47	95	●	●
11.20	11.2	47	102	○	●
11.30	11.3	47	102	○	●
11.50	11.5	47	102	●	●
11.80	11.8	47	102	○	●
12.00	12	51	102	●	●
12.20	12.2	51	102	○	●
12.50	12.5	51	103	●	●
12.80	12.8	51	103	○	●
13.00	13	51	103	●	●
13.50	13.5	54	107	●	●
13.80	13.8	54	107	○	●
14.00	14	54	107	●	●
14.50	14.5	56	111	●	●

● stock standard ○ non-standard stock ■ stock exhaustion

- TYPHOON
- C-SD-TA
- LFTA
- SUTA
- HSS-HSS/CO DRILLS
- UH RED
- MEX ORANGE
- HF EVO
- MEF ENDLESS
- ALU
- MDC
- G2
- MDTA
- ULTRA MILLS
- HSS/CO
- CARBIDE BURRS
- PARAMETERS