

n **Vf**
PAGE 248


DIN
1897

218LFTA



218LFTA (h8)

Ø mm	1~3	3.1~6	6.1~10	10.1~18	18.1~20
tol. D µ	0 / -14	0 / -18	0 / -22	0 / -27	0 / -33



d = D



D(h8)	I	L	Stock
mm 9.20	40	84	●
9.30	40	84	●
9.40	40	84	●
9.50	40	84	●
9.60	43	89	●
9.70	43	89	●
9.80	43	89	●
9.90	43	89	●
10.00	43	89	●
10.20	43	89	●
10.30	43	89	●
10.50	43	89	●
10.80	47	95	●
11.00	47	95	●
11.20	47	95	●
11.30	47	95	●
11.50	47	95	●
11.80	47	95	●
12.00	51	102	●
12.20	51	102	●
12.50	51	102	●
12.80	51	102	●
13.00	51	102	●
13.30	54	107	●
13.50	54	107	●
13.80	54	107	●
14.00	54	107	●
14.50	56	111	●
14.80	56	111	●
15.00	56	111	●
15.30	56	111	●
15.50	58	115	●
15.80	58	115	●
16.00	58	115	●
16.50	60	119	●
17.00	60	119	●

● stock standard ○ non-standard stock ■ stock exhaustion