

n **Vf**
PAGE 249


DIN 338

238LFTA



238LFTA (h8)

Ø mm	1~3	3.1~6	6.1~10	10.1~18	18.1~20
tol. D µ	0 / -14	0 / -18	0 / -22	0 / -27	0 / -33



d = D



D(h8)	I	L	Stock
mm 5.60	57	93	●
5.70	57	93	●
5.80	57	93	●
5.90	57	93	●
6.00	57	93	●
6.10	63	101	●
6.20	63	101	●
6.30	63	101	●
6.40	63	101	●
6.50	63	101	●
6.60	63	101	●
6.70	63	101	●
6.80	69	109	●
6.90	69	109	●
7.00	69	109	●
7.10	69	109	●
7.20	69	109	●
7.30	69	109	●
7.40	69	109	●
7.50	69	109	●
7.60	75	117	●
7.70	75	117	●
7.80	75	117	●
7.90	75	117	●
8.00	75	117	●
8.10	75	117	●
8.20	75	117	●
8.30	75	117	●
8.40	75	117	●
8.50	75	117	●
8.60	81	125	●
8.70	81	125	●
8.80	81	125	●
8.90	81	125	●
9.00	81	125	●
9.10	81	125	●

● stock standard ○ non-standard stock ■ stock exhaustion

TYPHOON
C-SD-TA
LFTA
SUTA
HSS-HSS/CO DRILLS
UH RED
MEX ORANGE
HF EVO
MEF ENDLESS
ALU
MDC
G2
MDTA
ULTRA MILLS
HSS/CO
CARBIDE BURRS
PARAMETERS