



**DIN
338**


PAGE 249

238LFTA



238LFTA (h8)

Ø mm	1~3	3.1~6	6.1~10	10.1~18	18.1~20
tol. D µ	0 / -14	0 / -18	0 / -22	0 / -27	0 / -33



d = D



**HSS/CO
PV10**



D(h8)	I	L	Stock
mm 9.20	81	125	●
9.30	81	125	●
9.40	81	125	●
9.50	81	125	●
9.60	87	133	●
9.70	87	133	●
9.80	87	133	●
9.90	87	133	●
10.00	87	133	●
10.20	87	133	●
10.30	87	133	●
10.50	87	133	●
10.80	94	142	●
11.00	94	142	●
11.20	94	142	●
11.30	94	142	●
11.50	94	142	●
11.80	94	142	●
12.00	101	151	●
12.20	101	151	●
12.50	101	151	●
12.80	101	151	●
13.00	101	151	●
13.30	108	160	●
13.50	108	160	●
13.80	108	160	●
14.00	108	160	●
14.50	114	169	●
14.80	114	169	●
15.00	114	169	●
15.30	120	178	●
15.50	120	178	●
15.80	120	178	●
16.00	120	178	●
16.50	125	184	●
17.00	125	184	●

● stock standard ○ non-standard stock ■ stock exhaustion