

n **Vf**
PAGE 249

**OSAWA
NORM**


3XD

980SUTA



980SUTA (h8)

| | | | | | |
|----------|---------|---------|---------|---------|---------|
| Ø mm | 1~3 | 3.1~6 | 6.1~10 | 10.1~18 | 18.1~20 |
| tol. D µ | 0 / -14 | 0 / -18 | 0 / -22 | 0 / -27 | 0 / -33 |



d = D



| D(h8) | I | L | Stock |
|---------|----|----|-------|
| mm 2.00 | 12 | 44 | ● |
| 2.10 | 12 | 44 | ● |
| 2.20 | 13 | 45 | ● |
| 2.30 | 13 | 45 | ● |
| 2.40 | 14 | 46 | ● |
| 2.50 | 14 | 46 | ● |
| 2.60 | 14 | 46 | ● |
| 2.70 | 16 | 48 | ● |
| 2.80 | 16 | 48 | ● |
| 2.90 | 16 | 48 | ● |
| 3.00 | 16 | 48 | ● |
| 3.10 | 18 | 50 | ● |
| 3.20 | 18 | 50 | ● |
| 3.30 | 18 | 50 | ● |
| 3.40 | 20 | 52 | ● |
| 3.50 | 20 | 52 | ● |
| 3.60 | 20 | 52 | ● |
| 3.70 | 20 | 52 | ● |
| 3.80 | 22 | 54 | ● |
| 3.90 | 22 | 54 | ● |
| 4.00 | 22 | 54 | ● |
| 4.10 | 22 | 66 | ● |
| 4.20 | 22 | 66 | ● |
| 4.30 | 24 | 68 | ● |
| 4.40 | 24 | 68 | ● |
| 4.50 | 24 | 68 | ● |
| 4.60 | 24 | 68 | ● |
| 4.70 | 24 | 68 | ● |
| 4.80 | 26 | 70 | ● |
| 4.90 | 26 | 70 | ● |
| 5.00 | 26 | 70 | ● |
| 5.10 | 26 | 70 | ● |
| 5.20 | 26 | 70 | ● |
| 5.30 | 26 | 70 | ● |
| 5.40 | 28 | 72 | ● |
| 5.50 | 28 | 72 | ● |

* ≤ mm 4 = 130°

● stock standard ○ non-standard stock ■ stock exhaustion