

n **Vf**
PAGE 249

**OSAWA
NORM**


3XD

980SUTA



980SUTA (h8)

Ø mm	1~3	3.1~6	6.1~10	10.1~18	18.1~20
tol. D µ	0 / -14	0 / -18	0 / -22	0 / -27	0 / -33



d = D

SUTA
HSSE
PV10
120°
38°

D(h8)	I	L	Stock
mm 5.60	28	72	●
5.70	28	72	●
5.80	28	72	●
5.90	28	72	●
6.00	28	72	●
6.10	31	75	●
6.20	31	75	●
6.30	31	75	●
6.40	31	75	●
6.50	31	75	●
6.60	31	75	●
6.70	31	75	●
6.80	34	78	●
6.90	34	78	●
7.00	34	78	●
7.10	34	78	●
7.20	34	78	●
7.30	34	78	●
7.40	34	78	●
7.50	34	78	●
7.60	37	81	●
7.70	37	81	●
7.80	37	81	●
7.90	37	81	●
8.00	37	81	●
8.10	37	87	●
8.20	37	87	●
8.30	37	87	●
8.40	37	87	●
8.50	37	87	●
8.60	40	90	●
8.70	40	90	●
8.80	40	90	●
8.90	40	90	●
9.00	40	90	●
9.10	40	90	●

● stock standard ○ non-standard stock ■ stock exhaustion

- TYPHOON
- C-SD-TA
- LFTA
- SUTA**
- HSS-HSS/CO DRILLS
- UH RED
- MEX ORANGE
- HF EVO
- MEF ENDLESS
- ALU
- MDC
- G2
- MDTA
- ULTRA MILLS
- HSS/CO
- CARBIDE BURRS
- PARAMETERS