

n **Vf**
PAGE 249

OSAWA
NORM


3XD

980SUTA



980SUTA (h8)

Ø mm	1~3	3.1~6	6.1~10	10.1~18	18.1~20
tol. D µ	0 / -14	0 / -18	0 / -22	0 / -27	0 / -33



d = D



D(h8)	I	L	Stock
mm 9.20	40	90	●
9.30	40	90	●
9.40	40	90	●
9.50	40	90	●
9.60	43	93	●
9.70	43	93	●
9.80	43	93	●
9.90	43	93	●
10.00	43	93	●
10.10	43	100	●
10.20	43	100	●
10.30	43	100	●
10.40	43	100	●
10.50	43	100	●
10.60	43	100	●
10.70	47	104	●
10.80	47	104	●
10.90	47	104	●
11.00	47	104	●
11.10	47	104	●
11.20	47	104	●
11.30	47	104	●
11.40	47	104	●
11.50	47	104	●
11.60	47	104	●
11.70	47	104	●
11.80	47	104	●
11.90	51	108	●
12.00	51	108	●
12.10	51	108	●
12.20	51	108	●
12.30	51	108	●
12.40	51	108	●
12.50	51	108	●
12.60	51	108	●
12.70	51	108	●

● stock standard ○ non-standard stock ■ stock exhaustion