

n **Vf**
PAGE 249

**OSAWA
NORM**


5XD

990SUTA



990SUTA (h8)

Ø mm	1~3	3.1~6	6.1~10	10.1~18	18.1~20
tol. D μ	0 / -14	0 / -18	0 / -22	0 / -27	0 / -33



d = D



D(h8)	I	L	Stock
mm 2.00	24	56	●
2.10	24	56	●
2.20	27	59	●
2.30	27	59	●
2.40	30	62	●
2.50	30	62	●
2.60	30	62	●
2.70	33	65	●
2.80	33	65	●
2.90	33	65	●
3.00	33	65	●
3.10	36	68	●
3.20	36	68	●
3.30	36	68	●
3.40	39	71	●
3.50	39	71	●
3.60	39	71	●
3.70	39	71	●
3.80	43	75	●
3.90	43	75	●
4.00	43	75	●
4.10	43	87	●
4.20	43	87	●
4.30	47	91	●
4.40	47	91	●
4.50	47	91	●
4.60	47	91	●
4.70	47	91	●
4.80	52	96	●
4.90	52	96	●
5.00	52	96	●
5.10	52	96	●
5.20	52	96	●
5.30	52	96	●
5.40	57	101	●
5.50	57	101	●

* ≤ mm 4 = 130°

● stock standard ○ non-standard stock ■ stock exhaustion