

n **Vf**
PAGE 249

**OSAWA
NORM**


5XD

990SUTA



990SUTA (h8)

Ø mm	1~3	3.1~6	6.1~10	10.1~18	18.1~20
tol. D µ	0 / -14	0 / -18	0 / -22	0 / -27	0 / -33



d = D

SUTA
HSSE
PV10
120°
38°

D(h8)	I	L	Stock
mm 5.60	57	101	●
5.70	57	101	●
5.80	57	101	●
5.90	57	101	●
6.00	57	101	●
6.10	63	107	●
6.20	63	107	●
6.30	63	107	●
6.40	63	107	●
6.50	63	107	●
6.60	63	107	●
6.70	63	107	●
6.80	69	113	●
6.90	69	113	●
7.00	69	113	●
7.10	69	113	●
7.20	69	113	●
7.30	69	113	●
7.40	69	113	●
7.50	69	113	●
7.60	75	119	●
7.70	75	119	●
7.80	75	119	●
7.90	75	119	●
8.00	75	119	●
8.10	75	125	●
8.20	75	125	●
8.30	75	125	●
8.40	75	125	●
8.50	75	125	●
8.60	81	131	●
8.70	81	131	●
8.80	81	131	●
8.90	81	131	●
9.00	81	131	●
9.10	81	131	●

● stock standard ○ non-standard stock ■ stock exhaustion

TYPHOON

C-SD-TA

LFTA

SUTA

HSS-HSS/CO DRILLS

UH RED

MEX ORANGE

HF EVO

MEF ENDLESS

ALU

MDC

G2

MDTA

ULTRA MILLS

HSS/CO

CARBIDE BURRS

PARAMETERS