

n **Vf**
PAGE 249

OSAWA
NORM


5XD

990SUTA



990SUTA (h8)

Ø mm	1~3	3.1~6	6.1~10	10.1~18	18.1~20
tol. D µ	0 / -14	0 / -18	0 / -22	0 / -27	0 / -33



d = D



D(h8)	I	L	Stock
mm 9.20	81	131	●
9.30	81	131	●
9.40	81	131	●
9.50	81	131	●
9.60	87	137	●
9.70	87	137	●
9.80	87	137	●
9.90	87	137	●
10.00	87	137	●
10.10	87	144	●
10.20	87	144	●
10.30	87	144	●
10.40	87	144	●
10.50	87	144	●
10.60	87	144	●
10.70	94	151	●
10.80	94	151	●
10.90	94	151	●
11.00	94	151	●
11.10	94	151	●
11.20	94	151	●
11.30	94	151	●
11.40	94	151	●
11.50	94	151	●
11.60	94	151	●
11.70	94	151	●
11.80	94	151	●
11.90	101	158	●
12.00	101	158	●
12.10	101	158	●
12.20	101	158	●
12.30	101	158	●
12.40	101	158	●
12.50	101	158	●
12.60	101	158	●
12.70	101	158	●

● stock standard ○ non-standard stock ■ stock exhaustion