



118N - 218NVA (h8)

Ø mm	1~3	3.1~6	6.1~10	10.1~18	18.1~20
tol. D µ	0 / -14	0 / -18	0 / -22	0 / -27	0 / -33



d = D

N

HSS

OX +

118°

25-30°

NH

HSS/CO

HT

130°

30°

D(h8)	I	L		Stock	Stock
mm 1.00	6	26	10	●	●
1.10	7	28	10	●	○
1.20	8	30	10	●	●
1.25	8	30	10	●	○
1.30	8	30	10	●	○
1.40	9	32	10	●	○
1.50	9	32	10	●	●
1.60	10	34	10	●	○
1.70	10	34	10	●	○
1.75	11	36	10	●	○
1.80	11	36	10	●	○
1.90	11	36	10	●	○
2.00	12	38	10	●	●
2.10	12	38	10	●	●
2.20	13	40	10	●	○
2.25	13	40	10	●	○
2.30	13	40	10	●	○
2.40	14	43	10	●	●
2.50	14	43	10	●	●
2.60	14	43	10	●	○
2.70	16	46	10	●	○
2.75	16	46	10	●	○
2.80	16	46	10	●	○
2.90	16	46	10	●	○
3.00	16	46	10	●	●
3.10	18	49	10	●	○
3.20	18	49	10	●	●
3.25	18	49	10	●	●
3.30	18	49	10	●	●
3.40	20	52	10	●	●
3.50	20	52	10	●	●
3.60	20	52	10	●	○
3.70	20	52	10	●	○
3.75	20	52	10	●	○
3.80	22	55	10	●	●
3.90	22	55	10	●	○

* OX ≥ mm. 2

● stock standard ○ non-standard stock ■ stock exhaustion