

n **Vf**
PAGE
250~252

DIN
338

238NVA - 2386STI (h8)

Ø mm	1~3	3.1~6	6.1~10	10.1~18	18.1~20
tol. D µ	0 / -14	0 / -18	0 / -22	0 / -27	0 / -33



d = D

D(h8)	I	L		Stock	Stock
mm 7.00	69	109	5	●	●
7.10	69	109	5	●	●
7.20	69	109	5	●	●
7.25	69	109	5	●	●
7.30	69	109	5	●	●
7.40	69	109	5	●	●
7.50	69	109	5	●	●
7.60	75	117	5	●	●
7.70	75	117	5	●	●
7.75	75	117	5	●	●
7.80	75	117	5	●	●
7.90	75	117	5	●	●
8.00	75	117	5	●	●
8.10	75	117	5	●	●
8.20	75	117	5	●	●
8.25	75	117	5	●	●
8.30	75	117	5	●	●
8.40	75	117	5	●	●
8.50	75	117	5	●	●
8.60	81	125	5	●	●
8.70	81	125	5	●	●
8.75	81	125	5	●	●
8.80	81	125	5	●	●
8.90	81	125	5	●	●
9.00	81	125	5	●	●
9.10	81	125	5	●	●
9.20	81	125	5	●	●
9.25	81	125	5	●	●
9.30	81	125	5	●	●
9.40	81	125	5	●	●
9.50	81	125	5	●	●
9.60	87	133	5	●	●
9.70	87	133	5	●	●
9.75	87	133	5	●	●
9.80	87	133	5	●	●
9.90	87	133	5	●	●

● stock standard ○ non-standard stock ■ stock exhaustion

- TYPHOON
- C-SD-TA
- LFTA
- SUTA
- HSS-HSS/CO DRILLS
- UH RED
- MEX ORANGE
- HF EVO
- MEF ENDLESS
- ALU
- MDC
- G2
- MDTA
- ULTRA MILLS
- HSS/CO
- CARBIDE BURRS
- PARAMETERS